

Desco Inc.(HQ/Manufacturer)

HEAD OFFICE: 1240-1, Ok-Dong, Gwangsan, Gwangju, Korea

TEL: 82.62.952.4564 / FAX: 82.62.953.1593

EXPORT DIVISION

2607 jidong, Lottecastle, 76, Soongin-Dong, Jongno-Gu, Seoul, Korea

TEL: 82-2-3670 6400 / FAX: 82-2-3670 6399

E-mail: desco@desco-inc,com





DS CARRIER DSC-400









DS Carrier 400 (Most simple & compact)

- * Full hydraulic system
- * Loading capacity 4 ton
- * Gradeability 30º (55%)
- * DS carrier can be used as power pack
- * Easy to mobile, easy to trun and rides on rubber tracks for less surfact disturbance
- * All instrument & control levers are concentrated.
- * Options mud pump, inverter, rod crane, self-loading system, pre-heating system, wireless remote control and so on

If you want the kind of drill rigs, DESCO INC. is at your solution and service.

DESCO INC. is at your solution and service.



TECHNICAL SPECIFICATION

| n | imensi | inn 8 | ₹ W | lein | ht |
|---|--------|-------|-----|------|----|
| | | | | | |

| Net weight | 3.0 ton |
|---------------------------------|---------|
| Width | 1.8M |
| Length (mast folded / unfolded) | 5.0M |
| Height (mast folded / unfolded) | 2.4M |

Engine

| Hyundai D4AK |
|--------------|
| 74HP@1800rpm |
| Water |
| 80 Liters |
| 24V DC |
| |

Hydraulic system

| Try at datile of octors | | |
|-------------------------|---|--|
| General | Single variable displacement pump, pressure & flow controlled | |
| Pump model | K3V30*2 (2 pumps) | |
| Hydraulic tank | 80 Liters | |
| Operating pressure | 280 Bar | |

Crawler base Desco model (Rubber)

| Clawler base | Desco model (nabbel) |
|------------------|-----------------------|
| Model | Desco model (Rubber) |
| Crawler Speed | Max. 4km/h |
| Loading capacity | 4.Oton |
| Gradeability | 30 ⁰ (55%) |

Auxiliary hydraulic ports (for power pack)

Optional list

- Rod Crane (1.2ton)
- · Mud pump
- · Inverter
- · Jacks & Riggers : Self-loading system
- · Preheating system
- Wireless remote travel
- · Steel track with rubber pad

Notice

As your optional list, engine, hyd. system, cralwer and so on

can be changed and design of drill rigs can be changed.

Specifications are general and subject to change without notice.

Due to selected options, delivered equipment may not necessarily match that shown.

